



FOVI F19S



TECHNICAL SPECIFICATIONS

Model Name	F19S
Cabinet Colour	Black
Pixel / Dot Pitch	0.3(H) × 0.3(V)mm
Display Area	409.8(H) × 230.4(V)mm
VIS	470mm
Brightness	250 cd/m ²
Contrast Ratio	10000:1 (DCR)
Response Time	5ms
Viewing Angle H / V	170/160(CR≥10)
Scanning Frequency	H:30~80KHz V:55~75Hz
Pixel Frequency	85.5MHz
Maximum Resolution	1366x768@60Hz
Recommended Resolution	1366x768@60Hz
Resolution Supported	640x480@60Hz 640x480@72Hz 640x480@75Hz 800x600@56Hz 800x600@60Hz 800x600@72Hz 800x600@75Hz 1024x768@60Hz 1024x768@70Hz 1024x768@75Hz 1366x768@60Hz
Display Colours	16.7M
Compatibility	VESA, VGA, SVGA, XGA, WXGA, Mac®
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive
Input Connector	Analog RGB Signal: 15-pin D-sub Male
Power Supply	Universal 100~240VAC, 50/60Hz
Power Consumption	On: 28Watts (Max.) Standby: < 1Watt
Plug & Play	DDC/2B, DDC/CI
User Control	Contrast/Left, ECO/Up, DCR/Right, Auto/Down, Power/Menu
OSD Languages	8 Languages
Speaker	No
Regulations	cULus, FCC, CE, Certified for Windows Vista Logo, ROHS, EPEAT Silver
Energy Star	Yes
Other Features	Aluminum Navigation Key, User Friendly Graphical OSD Menu, VESA 100mm Wall Mount Compliant*, Kensington Security Slot, includes AOC proprietary i-Menu software OSD
Dimensions (Monitor)	445.8 * 334.3 * 79.9 mm
Dimensions (Carton)	508 * 394 * 150 mm
Weight (Net / Gross)	3.7Kg / 4.8 Kg
Loading Qty w/pallet	1806 / 840
EAN Code	471 120099089 8

Note: Specifications are subject to change without notice.

*Wall mount arm & bracket not included.

Windows and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.